

KTZ1000S36

36x Optical Zoom

OUTDOOR WALL MOUNT



Specifications

Image Sensor	1/4" CCD SENSOR SONY ExView HAD CCD
Picture Pixels	NTSC: 768(H) x 494(V) PAL : 752(H) x 582(V)
Scanning System	2 : 1 Interlace
Horizontal Frequency	15.750 Khz/NTSC 15.625 Khz/PAL
Vertical Frequency	60 Hz/NTSC 50 Hz/PAL
Video Output	1 Vpp , 75 ohms
Horizontal Resolution	540 TVL
Gamma correction	0.45
Minimum Illumination	0.1 Lux / F1.6 (Color) 0.001 Lux / F1.6 (Mono)
S/N Ratio	>50dB
Zoom	36x Optical / 432x Digital F = 3.4mm -122.4mm F1.6 to F4.5
Receiver Data	Built-In RS485 Interface
Angle of View (H)	57.8 to 1.7 (degree)
Preset / Preset Speed	128 Preset Points / 280° / sec
Power Source	AC24V / 2A
Weather Resistant	IP66
Operation Temp.	-40 to +60 Deg. C
Weight	7.3 Kg

SONY HAD

● Features

- High Resolution SONY ExView
- Day/Night high speed Dome
- Starlight Mode of 0.001 Lux B/W
- 36X Optical Zoom with Auto-Flip
- Auto Zoom speed control auto-adjusted according to zoom length changing
- 360° Continuous Pan Rotation
- Built-in Back-Light Compensation